


HAND HELD PNEUMATIC BREAKER

เครื่องสัดลม



PICK HAMMER


- Light weight and easy to handle.
- Automatic throttle type.
- A few components for easy maintenance.
- Forged body for long life.
- Simple structure for less maintenance.
- Long stroke cylinder provides maximum impact energy.
- Replaceable round bushing.
- Reinforced cup retainer.



*Round Shank (Moil Point Chisel)



*Round Shank (Flat Chisel)



*Round Shank (Asphalt Cutter)



MODEL NO.	PISTON DIAMETER mm	PISTON STROKE mm	BLOW PER MIN. b.p.m.	NET WEIGHT kg lb	OVERALL LENGTH mm	AIR CONSUMPTION m ³ /min c.f.m.	HOSE SIZE mm	SHANK SIZE ROUND OR HEX	AIR INLET SIZE PT
CA-7	35	120	1,250	7.2 15.8	465	1 35.3	19	R26×80	3/4
CB-130B	35	130	1,400	15 33	490	1.05 37.1	19	R26×80	1
CB-20	40	165	1,100	21.2 46.2	556	1.4 49.4	19	R30×87	1
CB-300	45	180	950	30 66	610	1.7 60	19	R35×87	1

CONCRETE BREAKER

- Alloy steel forged parts provide maximum durability.
- Anti-vibration models are available for workers health care.
- Forged Latch retainer for quick chisel change.



*Hex Shank (Moil Point Chisel)



*Hex Shank (Flat Chisel)



MODEL NO.	PISTON DIAMETER mm	PISTON STROKE mm	BLOW PER MIN. b.p.m.	NET WEIGHT kg lb	OVERALL LENGTH mm	AIR CONSUMPTION m ³ /min c.f.m.	HOSE SIZE mm	SHANK SIZE ROUND OR HEX	AIR INLET SIZE PT
TPB-30	44.45	85	1,550	15 33	564	1.4 49.4	12.7	7/8×3-1/4 or 1×4-1/4	1/2
TPB-40	44	146	1,100	18 39.6	660	1.6 56.5	19	1×4-1/4	3/4
TPB-60	57.15	100	1,400	30 66	645	2 70.6	19	1-1/8×6 or 1-1/4×6	3/4